



**OT-2208SIW**  
8 Ports 10/100Mbps WEB Smart Switch

## Product Description

The OT-2208SIW Switch fully complies with IEEE 802.3/802.3u Ethernet standards. It provides 8 10/100Mbps RJ45 ports with auto-MDI/MDIX. It also provides software management functions including the system, port network, VLAN, Trunk and security etc.

## Product Features

- Supports IEEE 802.3x flow control for Full Duplex mode and backpressure for Half Duplex mode
- 8 10/100Mbps Auto-Negotiation RJ45 ports supporting Auto-MDI/MDIX
- Supports Port-Based VLAN
- Supports Port Bandwidth Control
- Supports trunking groups
- Supports the configuration function of Port Security, Broadcast Storm Control
- Supports MAC address auto-learning and auto-aging
- Supports Static Port Priority
- External power adapter supply

## Product Specifications

<b>Protocols and Standards</b>		IEEE 802.3 IEEE 802.3u
<b>Ports</b>		8 10/100M Auto-Negotiation RJ45 Ports (Auto MDI/MDIX)
<b>Network Media</b>		10Base-T: UTP category 3, 4, 5 cable (maximum 100m) EIA/TIA-568 100Û STP (maximum 100m) 100Base-Tx: UTP category 5, 5e cable (maximum 100m) EIA/TIA-568 100Û STP (maximum 100m)
<b>LED Indicators</b>	<b>Each port</b>	Link/Act; 100Mbps
	<b>Power</b>	Power
<b>Backbound Bandwidth</b>		1.6Gbps
<b>Forwarding Rate</b>		10BASE-T: 14880pps/port 100BASE-TX: 148800pps/port
<b>MAC Address Table</b>		1k
<b>Transmission Method</b>		Store-and-Forward
<b>Dimensions (W×D×H)</b>		175mm x 124.2mm x 29.8mm
<b>Environment</b>		Operating Temperature: 0□~40□ (32□~104□) Storage Temperature: -40~70□ (-40□~158□) Operating Humidity: 10%~90% non-condensing Storage Humidity: 5%~95% non-condensing
<b>Power Input</b>		External Power Adapter

